



Sparkling Light Publisher

Sparklinglight Transactions on Artificial Intelligence and Quantum Computing (STAIQC)



Website: <https://sparklinglightpublisher.com/> ISSN (Online):2583-0732

A Short Contemporary Survey on Covid-19 Diagnosis

Bin Li^{a,*}, Mackenzie Brown^b

^a*School of Computer Science and Technology, Henan Polytechnic University, Jiaozuo, Henan 454000, P R China*

^b*School of Data Science, Perdana University, Serdang 43400, Selangor, Malaysia*

Abstract

As the new crown pneumonia epidemic continues to worsen, traditional diagnosis cannot satisfy the demand of the detection of disease. Therefore, it becomes necessary to use artificial intelligence to assist medical treatment to achieve efficient and accurate judgments. At present, deep learning is becoming more and more mature in the domain of medical image, which is capable to offer quicker, cheaper and safer diagnostic service for the person infected by COVID-19. This paper offers a comprehensive summary of the latest approaches and applications of deep learning in the domain of COVID-19. We summarized and analyzed some COVID-19 detection methods and models. Through research and analysis, deep learning can provide accurate and efficient diagnosis for COVID-19 classification.

© 2021 STAIQC. All rights reserved.

Keywords: COVID-19; Classification; Deep learning.

1. Introduction

In traditional virus detection, each suspected case needs to be verified by RT-PCR(Reverse Transcription-Polymerase Chain Reaction) [1]. But it takes a lot of time to perform RT-PCR, and the false negative rate is high [2]. CT (Computed Tomography) images and X-ray images are useful for medical evaluation of pulmonary imaging and treatment in people infected with COVID-19. Chest CT images and X-ray images provide a wealth of pathological information, but the lack of computers to accurately quantify infected areas and its pathological changes has hindered healthcare providers from providing diagnostic screening quickly. Feng Yu et al. [3] proposed a lung nodule recognition approach which is based on a three-dimensional convolutional neural network considered lots of false positives in lung nodule detection in traditional computer-aided detection systems. Ma Yuan et al. [4] used deep belief nets to identify benign and malignant lung nodules in CT images. Huang Sheng et al. [5] proposed a CT image pattern classification model more suitable for lung tissue based on the improved deep residual network.

E-mail address of authors: ^a*libin@home.hpu.edu.cn*, ^b*mackbrown@ieee.org*.

© 2021 STAIQC. All rights reserved.

Please cite this article as: Please cite this article as: Bin li, & Mackenzie Brown (2021). A Short Contemporary Survey on Covid-19 Diagnosis. *Sparklinglight Transactions on Artificial Intelligence and Quantum Computing*, 1(2), 21-25. ISSN (Online):2583-0732. Received Date: 28/07/2021, Reviewed Date: 80/08/2021, Published Date: 24/08/2021.

Artificial intelligence is used to rapidly analyze case characteristics, detect CT and X-ray chest images for any abnormalities, and provide clinicians with further diagnosis for treatment or isolation. Shalu C et al. [6] adopted convolutional neural networks to recognize motion image formation task, but did not consider the influence of hyperparameters with classification performance. Ma M et al. [7] presented the k-means clustering initialization hyperparameter algorithm, which improved the accuracy of network recognition and accelerated the network training process. Ijjina E P et al. [8] used genetic algorithm to improve the hyperparameters of the network to minimize classification error. The hyper-parameter automatic selection method refers to the calculation and statistics method in the selection process using the high-performance accelerated model. Bayesian optimization is employed to automatically search for best hyper-parameters of deep convolution to configure the network. Wang Y et al. [9] adopted PSO algorithm to optimize and modify the structure of CNN and determine the configuration of hyperparameters. Although the current optimization algorithms can exhibit different optimize ability, complexity, exploratory efficiency, hyper-parameter optimization is always deserved to research and exploration.

2. Methods and Results

The development of AI-based automated CT and X-ray image analysis tools for coronavirus detection, quantification, and tracking is essential for epidemic control. There have been some studies on COVID-19 screening and prediction tasks, which mainly use deep learning model to extract features and achieve classification task of CT images and X-ray images to distinguish coronavirus patients from non-patients. In this way, a non-contact method based on pathological principles can be used for COVID screening, and the risk of doctors being infected by patients is reduced [10]. In deep learning [11-13], there are many network structures that can be used to achieve COVID-19 classification. Such as ResNet, VGG, DenseNet, Inception, GoogleNet, MobileNet, Xception, etc. The classifiers include SVM, ELM, Softmax, etc.

Traditional network structure has good performance for the classification and recognition of new coronary pneumonia. Wang et al., [14] implemented an automated deep learning system for coronavirus diagnosis and prognosis analysis. This experiment was carried out on two data sets. The highest sensitivity and maximum specificity of the experiments in the two data sets were 80.3% and 81.1%. What they use is the DenseNet network. DenseNet directly connects layers to enhance feature transfer and make more efficient use of features. Li et al. distinguished between community-acquired pneumonia and new coronary pneumonia on chest CT. Sensitivity was 90% and specificity was 96%. They use the ResNet-50 residual network, which uses skip-connected residual blocks to alleviate the problem of vanishing gradients, so it is easier to build a deeper network to improve performance. Saiz and Barandiaran, [17] adopted deep learning methods to achieve coronavirus disease detection in chest images of x-ray. Accuracy is 94.92%, sensitivity is 94.92%, and specificity is 92%. The network they use is VGG network. The deep network structure, small convolution kernel and pooling sampling domain of the VGG model enable it to get more features while controlling the quantity of parameters, thereby avoiding too much calculation and too complicated structure. The VGG model performs well in multiple transfer learning tasks. Wu et al., [23] also used the VGG-19 network to screen and diagnose COVID-19. Its disadvantage is that there are too many parameters and more storage space is required. Waheed et al., [18] used the auxiliary classifier GAN to enhance data and improve COVID-19 detection. Accuracy is 95%, sensitivity is 90%, and specificity is 97%. Song et al., et al., [20] realized the end-to-end automatic identification between coronavirus disease and viral pneumonia. Sensitivity was 85% and specificity was 88%.

In addition, there are some new network structures for the identification of coronavirus disease which have achieved good performance. Ni et al., [16] proposed a DL method to describe the features of pneumonia in chest images of CT, with a sensitivity of 100%, and a sensitivity of 0.96% for detecting each patient with lung disease. The models used are MVP-Net and 3D U-Net. Apostolopoulos et al., [21] used the MobileNetV2 network for COVID-19 classification and identification. MobileNet is a new model based on deep separable convolution, which has advantages in scale, calculation and speed. Das et al., [22] uses Truncated inceptionNet network for filtering (diagnosis). Wu et al., [24] used WRE and proposed a 3SBBO to achieve the target. Wang et al. [25] presented a fusion of GCN and FGC for the classification. Satapahty et al. [26] presented a five-layer CNN (5l-CNN) to diagnosis images. Zhu et al. [27] adopted an ANC network to identify COVID-19. Zhang et al. [28] presented a MIDCAN method that fuse both CT images and X-ray images to diagnose the coronavirus disease.

3. Discussion and conclusion

COVID-19 identification [29-31] is a classification task. The method used to assess classification performance included Precision, Recall, Sensitivity, Accuracy, F1 Score, etc.

Precision is the proportion of correct judgment in all positive samples.

$$Precision = \frac{TP}{TP+FP} \quad (1)$$

Sensitivity refers to the proportion of all correctly predicted positive samples to all actual positive samples, which is used to measure the ability to recognize positive examples.

$$Sensitivity = Recall = \frac{TP}{TP+FN} \quad (2)$$

Specificity refers to the ratio of all negative samples accurately predicted to all actual negative samples, which is used to measure the ability to recognize negative samples.

$$Specificity = \frac{TN}{TN+FP} \quad (3)$$

Accuracy refers to the percentage of the number of samples that are correctly predicted in all experiments.

$$accuracy = \frac{TP+TN}{TP+FP+FN+TN} \quad (4)$$

F1 Score is the harmonic average of the accuracy and recall of the model.

$$F1 = \frac{2 \cdot Precision \cdot Recall}{Precision + Recall} \quad (5)$$

In this article, we describe several methods for COVID-19 identification using the images of CT and X-ray. In addition, we summarize the characteristics of these methods in

Table 1.

Table 1 Some deep learning algorithms for COVID-19 diagnosis and detection

Author	Method used	Model	DataSet	Results	Aim of study
Wang et al., [14]	Deep learning(DL)	DenseNet121-FPN	5372 (two datasets)CT images	sensitivity: 80.3% and 79.35%, specificity: 76.3% and 81.1%	Diagnosis and prognosis
Li et al., [15]	DL	ResNet-50 as backbone of main mode	4356 CT exams from 3322 patients	Sensitivity: 90%, specificity: 96%	Diagnosis
Ni et al., [16]	CNN	3D U-Net, MVP-Net	14531 Images of CT	Lobe lesion: 0.96%, sensitivity: 100%	Detection

Saiz and Barandiaran,[17]	DL	transfer learning with VGG-16 SDD	1500 Images of X-ray	sensitivity: 94.92%, Accuracy: 94.92%	Detection
Waheed et al., [18]	GAN	VGG-16 and ACGAN3	1124 images of X-ray	sensitivity: 90%, Accuracy: 95%	Detection
Mei et al., [19]	DL	Inception_ResNet_V2	905 Images of CT	Accuracy: 68%	Diagnosis
Song et al., [20]	DL	BigBiGAN1	227 Images of CT	Specificity is 88%, Sensitivity is 85%	Detection
Apostolopoulos et al., [21]	DL	MobileNetV2	455 Images of X-ray	Accuracy is 99.18%, Sensitivity is 97.36%	Classification (detection)
Das et al., [22]	CNN	Truncated inception net	6845 Images of X-ray	Sensitivity is 88%,	Screening (diagnosis)
Wu et al., [23]	DL	VGG-19	495 Images of CT	Sensitivity is 81.1%, Accuracy is 76.0%	Screening (diagnosis)
Wu et al. [24]	Machine learning	WRE-3SBBO	296 CT images	Sensitivity: 86.40% Specificity: 85.81% Accuracy: 86.12%	Diagnosis
Wang et al. [25]	Deep learning	FGC	640 CT images	Sensitivity: 97.71% Specificity: 96.56% Accuracy: 97.14%	classification
Satapahty et al. [26]	Deep Learning	5l-CNN	640 CM Images	Sensitivity: 93.28% Specificity: 94.00% Accuracy: 93.64%	Diagnosis
Zhu et al. [27]	Deep Learning	ANC	640 CT images	Sensitivity: 95.88% Specificity: 96.13% Accuracy: 96.00%	Diagnosis
Zhang et al. [28]	Deep learning	MIDCAN	Both X-ray and CT-images	Sensitivity: 98.10% Specificity: 97.95% Accuracy: 98.02%	Diagnosis

From the Table 1, it can be seen that MVP-Net, 3D U-Net, FGC, MIDCAN, ANC, and the lightweight network MobileNetV2 have relatively excellent performance in COVID-19 classification. In the future, we will discuss more ways to identify COVID-19. There are some other COVID-19 related papers [32-35], we will analyze them in our future studies.

References

- [1] A. Anantharajah, R. Helaers, J. P. Defour, N. Olive, F. Kabera, L. Croonen, *et al.*, "How to choose the right real-time RT-PCR primer sets for the SARS-CoV-2 genome detection?," *Journal of Virological Methods*, vol. 295, Article ID: 114197, 2021.
- [2] J. R. Brown, D. M. O'Sullivan, D. Shah, L. Atkinson, R. P. A. Pereira, A. S. Whale, *et al.*, "Comparison of SARS-CoV-2 N gene real-time RT-PCR targets and commercially available mastermixes," *Journal of Virological Methods*, vol. 295, Article ID: 114215, 2021.
- [3] Y. B. S. Feng Y, Wu C Y, et al, "Pulmonary nodule recognition based on three-dimensional convolution neural network[J]," *Acta Optica Sinica*, 2019.

- [4] W. F. Ma Y, Han Y, et al, "Classification of pulmonary nodule on PET/CT image based on deep belief network[J]," *Chin J Med Imaging Technol*, 2020.
- [5] L. F. F. Huang S, Chen Q, "Computed tomography image classification algorithm based on improved deep residual network[J]," *Acta Optica Sinica*, 2020.
- [6] S. T. Shalu C, Varun B, et al, "Convolutional neural network based approach towards motor imagery tasks EEG signals classification[J]," *IEEE Sensors Journal*, 2019.
- [7] L. L. Ma M, Chen Y L, "A KM-net model based on kmeans weight initialization for images classification[C]," *2018 IEEE 20th International Conference on High Performance Computing and Communications, Exeter, United Kingdom*, 2018.
- [8] C. K. M. Ijjina E P, "Human action recognition using genetic algorithms and convolutional neural networks[J]," *Pattern Recognition*, 2016.
- [9] Z. H. Wang Y, Zhang G, "c PSO-CNN: An efficient PSO-based algorithm for fine-tuning hyper-parameters of convolutional neural networks[J]," *Swarm and Evolutionary Computation*, 2019.
- [10] S. H. Y. Yuan, "Introduction to the Special Issue on Computer Modelling of Transmission, Spread, Control and Diagnosis of COVID-19," *Computer Modeling in Engineering & Sciences*, vol. 127, pp. 385-387, 2021.
- [11] H. C. Reis, "COVID-19 Diagnosis with Deep Learning," *Ingenieria E Investigacion*, vol. 42, Article ID: e88825, 2022.
- [12] Y. Zhang and J. M. Gorriz, "Deep Learning in Medical Image Analysis," *Journal of Imaging*, vol. 7, p. 74, 2021.
- [13] G. F. Yeung, D. Borowiec, R. Y. Yang, A. Friday, R. Harper, and P. Garraghan, "Horus: Interference-Aware and Prediction-Based Scheduling in Deep Learning Systems," *IEEE Transactions on Parallel and Distributed Systems*, vol. 33, pp. 88-100, 2022.
- [14] S. Wang, Y. Zha, W. Li, Q. Wu, X. Li, M. Niu, et al., "A fully automatic deep learning system for COVID-19 diagnostic and prognostic analysis," *European Respiratory Journal*, vol. 56, p. 2000775, 2020.
- [15] L. Li, L. Qin, Z. Xu, Y. Yin, X. Wang, B. Kong, et al., "Using Artificial Intelligence to Detect COVID-19 and Community-acquired Pneumonia Based on Pulmonary CT: Evaluation of the Diagnostic Accuracy," *Radiology*, vol. 296, pp. E65-E71, 2020.
- [16] Q. Ni, Z. Y. Sun, L. Qi, W. Chen, Y. Yang, L. Wang, et al., "A deep learning approach to characterize 2019 coronavirus disease (COVID-19) pneumonia in chest CT images," *European Radiology*, vol. 30, pp. 6517-6527, 2020.
- [17] I. B. Fátima A. Saiz*, "COVID-19 Detection in Chest X-ray Images using a Deep Learning Approach," 10 April 2020.
- [18] A. Waheed, M. Goyal, D. Gupta, A. Khanna, F. Al-Turjman, and P. R. Pinheiro, "CovidGAN: Data Augmentation Using Auxiliary Classifier GAN for Improved Covid-19 Detection," *IEEE Access*, vol. 8, pp. 91916-91923, 2020.
- [19] X. Mei, H.-C. Lee, K.-y. Diao, M. Huang, B. Lin, C. Liu, et al., "Artificial intelligence-enabled rapid diagnosis of patients with COVID-19," *Nature Medicine*, vol. 26, pp. 1224-1228, 2020.
- [20] J. Song, H. Wang, Y. Liu, W. Wu, G. Dai, Z. Wu, et al., "End-to-end automatic differentiation of the coronavirus disease 2019 (COVID-19) from viral pneumonia based on chest CT," *European Journal of Nuclear Medicine and Molecular Imaging*, vol. 47, pp. 2516-2524, 2020.
- [21] I. D. Apostolopoulos and T. A. Mpesiana, "Covid-19: automatic detection from X-ray images utilizing transfer learning with convolutional neural networks," *Physical and Engineering Sciences in Medicine*, vol. 43, pp. 635-640, 2020.
- [22] D. Das, K. C. Santosh, and U. Pal, "Truncated inception net: COVID-19 outbreak screening using chest X-rays," *Physical and Engineering Sciences in Medicine*, vol. 43, pp. 915-925, 2020.
- [23] X. Wu, H. Hui, M. Niu, L. Li, L. Wang, B. He, et al., "Deep learning-based multi-view fusion model for screening 2019 novel coronavirus pneumonia: A multicentre study," *European Journal of Radiology*, vol. 128, p. 109041, 2020.
- [24] X. Wu, "Diagnosis of COVID-19 by Wavelet Renyi Entropy and Three-Segment Biogeography-Based Optimization," *International Journal of Computational Intelligence Systems*, vol. 13, pp. 1332-1344, 2020.
- [25] S.-H. Wang, "Covid-19 Classification by FGCNet with Deep Feature Fusion from Graph Convolutional Network and Convolutional Neural Network," *Information Fusion*, vol. 67, pp. 208-229, 2021.
- [26] S. C. Satapathy, "A five-layer deep convolutional neural network with stochastic pooling for chest CT-based COVID-19 diagnosis," *Machine Vision and Applications*, vol. 32, Article ID: 14, 2021.
- [27] W. Zhu, "ANC: Attention Network for COVID-19 Explainable Diagnosis Based on Convolutional Block Attention Module," *Computer Modeling in Engineering & Sciences*, vol. 127, pp. 1037-1058, 2021.
- [28] Z. Zhang and X. Zhang, "MIDCAN: A multiple input deep convolutional attention network for Covid-19 diagnosis based on chest CT and chest X-ray," *Pattern Recognition Letters*, vol. 150, pp. 8-16, 2021.
- [29] V. Zarezade, H. Rezaei, G. Shakerinezhad, A. Safavi, Z. Nazeri, A. Veisi, et al., "The identification of novel inhibitors of human angiotensin-converting enzyme 2 and main protease of Sars-Cov-2: A combination of in silico methods for treatment of COVID-19," *Journal of Molecular Structure*, vol. 1237, Article ID: 130409, 2021.
- [30] A. H. Almaghrebi, "Risk factors for attempting suicide during the COVID-19 lockdown: Identification of the high-risk groups," *Journal of Taibah University Medical Sciences*, vol. 16, pp. 605-611, 2021.
- [31] K. Mani, K. Thirumalmuthu, D. S. Kathiresan, S. Ramalingam, R. Sankaran, and S. Jeyaraj, "In-silico analysis of Covid-19 genome sequences of Indian origin: Impact of mutations in identification of SARS-Co-V2," *Molecular and Cellular Probes*, vol. 58, Article ID: 101748, 2021.
- [32] S.-H. Wang, "COVID-19 classification by CCSHNet with deep fusion using transfer learning and discriminant correlation analysis," *Information Fusion*, vol. 68, pp. 131-148, 2021.
- [33] S. C. Satapathy. (2021). Covid-19 diagnosis via DenseNet and optimization of transfer learning setting. *Cognitive Computation*. doi: 10.1007/s12559-020-09776-8
- [34] X. Cheng, "PSSPN: PatchShuffle Stochastic Pooling Neural Network for an Explainable Diagnosis of COVID-19 with Multiple-Way Data Augmentation," *Computational and Mathematical Methods in Medicine*, vol. 2021, Article ID: 6633755, 2021.
- [35] D. Anderson, "Deep fractional max pooling neural network for COVID-19 recognition," *Frontiers in Public Health*, vol. 9, Article ID: 726144, 2021.
